



STANDARD FEATURES



Control panel	ELECTRONIC DIGIT2
Wash arm	2 - Stainless steel
Rinse arm	2 - PP
Detergent injector	Optional
Rinse aid injector	Standard
Peristaltic rinse aid injector	Optional
Break tank	Optional
Water softener	Optional
Drain pump	Optional
Diagnose Wi-Fi	-

TECHNICAL FEATURES

External size	473x513x689	LxPxH	[mm]
Overall size	855	DOA	[mm]
Clearance	295	A	[mm]
Maximum height for crockery	280	Au	[mm]
Rack size	400x400		[mm]
Tank size	14		[lt]
Rinse water consumption	2,4		[lt]
Wash pump	0,27		[kW]
Tank heater element	1,6		[kW]
Booster heater element	2,8		[kW]
Installed load	3,1		[kW]
Cycles	60 / 120 / 180 / 480		[sec]
Output cycles per hour	60 / 30 / 20 / 8		[cycle/h]
Electrical supply	230V/50Hz		
Noise	48		[dBA]
Weight	34		[kg]

Theoretical data with water supply at 55°C
 Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C
 Dimension depending on the type of basket used.



STANDARD EQUIPMENT

Hoses (1 for each) Water connection, drain, transparent for rinse product
Baskets 1x8 plates, 1 universal basket, 1 cutlery rack

GENERAL FEATURES

- Double-skinned cabinet and door.
- Tank and door made of stainless steel AISI 304.
- Monobloc wash pump fixed directly to the tank.
- Easy-clean dual-filter system.
- Pressed basket guides in the tank.
- Two stainless-steel washing arms and two rinse arms of composite material, independent and rotary.
- Integral rinse aid dosing unit.
- Digital control panel (DIGIT2).
- Four purpose-designed wash cycles for various types of crockery to be washed.
- Cold for rinse programme for beer glasses.

PERFORMANCES

	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Supply water temperature												
Maximum cycles feasible in continuous operation	48	23	25	27	29	32	36	41	48	48	48	[rack/h]
Total spending power from single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Total spending power from double-skin machine	3,07	3,03	3,03	3,02	3,02	3,01	3,09	3,08	3,07	3,07	3,07	[kW]
Sensible heat emitted into the room from single-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the room from double-skinned machine	0,38	0,44	0,44	0,43	0,43	0,42	0,41	0,40	0,38	0,38	0,38	[kW]
Latent heat emitted into the room	0,61	0,14	0,17	0,20	0,24	0,29	0,36	0,44	0,56	0,61	0,67	[kW]
Emitted standby power with closed door in single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Emitted standby power with closed door in double-skin machine	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	[kW]